Fax sent by 3127048023 TREXLER, ETAL. 08-01-06 15:04 Pg: 5/19

Amendments to the Claims:

1-7. (canceled)

(Currently Amended) Self-locking fastening device comprising for engaging a screw or 8.

nut for fastening at least a first member to another member, wherein the fastening device is

provided with comprises a washer (10, 10') having a central bore hole (11, 11') which on the

and two surfaces thereof is provided with having rib profiles (12, 14; 12', 14') which are fixed

within or to the surfaces of the first member and the screw or nut no later than the time that the

fastening device screw or nut is tightened such that a self-actuated unscrewing is prevented and is

configured in such a resilient manner that it can be compressed counter to its resilience thereof by

being cambered chamfered, wherein the concave side is facing the member and the convex side

is facing the screw head or the nut, respectively, characterized in that the rib profiles (12, 14; 12',

14) on the surface facing the screw or nut are positioned in the inner area close to proximate the

bore hole (11, 11') and on the side facing the member in the exterior area elose proximate to the

an exterior margin edge of the washer and that the rib profiles (12, 14; 12', 14') each are

extending over the half up to two thirds of the radial extend over at least half and at most two

thirds of the width of the shim washer, said width being an area between the bore hole and the

exterior edge of the washer.

Serial No. 10/511,132

Art Unit: 3677

Page 2

Fax sent by 3127048023 TREXLER, ETAL. 08-01-06 15:04 Pg: 6/19

9. (Currently Amended) Fastening device according to claim 8, characterized in that the shim washer (10') only in its exterior marginal area is cambered chamfered in the radial direction while it is flat in the interior.

10. (Currently Amended) Fastening device according to claim 9, characterized in that the cambered chamfered outer marginal area only is extending over the half width of the shim extends only over half the width of the washer (10'), between its the inner bore hole (11') and the exterior margin edge of the washer.

Serial No. 10/511,132

Art Unit: 3677

Page 3